



Certificate number: 2311751 (2)

Issued 22/11/2023
Expires 01/04/2024

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)
Model number(s) – see Appendix

Bonomi Industries s.r.l.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Bonomi Industries s.r.l
Via Padana Superiore 29
I-25080 Mazzano (BS)
Italy



KUKreg4

Product Certificate

Appendix to Certificate number: 2311751

The following products belong to this certificate

<p>PRODUCT DESCRIPTION s.20, s.24 & s.28 range of in-line lever operated spherical valves with DZR brass bodies, chromium plated balls, PTFE seats and FKM `O` rings. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) S20XYZ: ¼" - 2" BSPP (FxF, MxF) INLET/OUTLET S24XYZ: ½" – 4" BSPP (FxF, MxF) INLET/OUTLET S28XYZ: 12MM - 54MM COMPRESSION INLET/OUTLET for use with copper tube to EN1057 Where: X = valve size. YY = type of thread and handle. Z = handle colour.</p>
<p>SIZE: See model.</p>
<p>SCOPE: Manufacturer recommended maximum working pressure s.20 and s.24 30.0 bar. Maximum working pressure s.28 16.0 bar. Maximum operating temperature 99°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.</p>
<p>MARKING CR, size & serial No. on body. RUB, made in Italy, model number & web address on lever. Pressure on body of s.20 & s.24 only.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge,</p>
<p>BACKFLOW PROTECTION NOTES N/A.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes